

# HIGH POWERED ANCHOR DRIVES SINGLE SPEED - 15-30T



## /// HIGH SPEED /// HIGH PERFORMANCE

*Digga's High Powered Drives operate at a **MAX PRESSURE OF 5,000 PSI** providing you the speed and performance without detuning your machine.*



**THE FASTEST DRIVE HEAD IN ITS CLASS**

### FEATURES

- COMPACT, HIGH QUALITY, DIGGA MADE GEARBOX
- BUILT-IN PRV (PRESSURE RELIEF VALVE) AS STANDARD
- ECV (ENERGY CONTROL RELIEF VALVE) TO PREVENT RAPID DECOMPRESSION OF OIL, CAUSED BY THE REVERSE ENERGY CREATED BY PILE KICK-BACK
- ENGINEERED HOOD & EARS FOR MAXIMUM STRENGTH
- EXTREME DUTY SHAFT LOCKING SYSTEM
- NO COMPLEX HOSES, VALVING OR FILTRATION
- 1YR GEARBOX & 1YR MOTOR WARRANTY

### OTHER MODELS AVAILABLE

- STANDARD 2 SPEED
- HIGH POWERED 2 SPEED
- HIGH POWERED AUTO SPEED (COMING SOON)

	SD HIGH POWERED - SINGLE SPEED				
MODEL	SD45HPS	SD50HPS	SD70HPS	SD80HPS	SD95HPS
Max Torque (ft-lbs)	33,654	39,463	51,634	62,638	69,244
Max Flow (Gpm)	100 GPM @ 3,500 PSI				
Max Pressure - Do Not Exceed	5,000 PSI @70 GPM				
Max Horse Power	201	201	201	201	201
Motor Type	Radial Piston	Radial Piston	Radial Piston	Radial Piston	Radial Piston
Pressure Relief Valve	Included	Included	Included	Included	Included
Energy Control Valve	Included	Included	Included	Included	Included
Standard Output Shaft	100mm Square	100mm Square	100mm Square	100mm Square	100mm Square

## OPTIONAL EXTRAS

- Ryno Piling cradle
- Drive Linkages
- Excavator Mounts/Hitch
- Diggalign - Pile/Auger Alignment system
- Torque Monitoring - Pressure Differential Gauge
- Torque Logic - Pile Alignment / Data Logging system / Torque Measuring



v1.01

# HIGH POWERED ANCHOR DRIVES

## SINGLE SPEED - 15-30T



### OUTPUT SPEED & TORQUE

SD45HPS				SD50HPS				SD70HPS				SD80HPS				SD95HPS			
OUTPUT SPEED		OUTPUT TORQUE		OUTPUT SPEED		OUTPUT TORQUE		OUTPUT SPEED		OUTPUT TORQUE		OUTPUT SPEED		OUTPUT TORQUE		OUTPUT SPEED		OUTPUT TORQUE	
GPM	RPM	PSI	FT-LBS	GPM	RPM	PSI	FT-LBS	GPM	RPM	PSI	FT-LBS	GPM	RPM	PSI	FT-LBS	GPM	RPM	PSI	FT-LBS
8	4	600	4,039	8	3	600	4,736	8	2	600	6,196	8	2	600	7,469	8	2	600	8,309
12	6	800	5,385	12	5	800	6,314	12	4	800	8,261	12	3	800	9,958	12	3	800	11,079
16	7	1,000	6,731	16	6	1,000	7,893	16	5	1,000	10,327	16	4	1,000	12,448	16	4	1,000	13,849
20	9	1,200	8,077	20	8	1,200	9,471	20	6	1,200	12,392	20	5	1,200	14,937	20	4	1,200	16,618
24	11	1,400	9,423	24	9	1,400	11,050	24	7	1,400	14,458	24	6	1,400	17,427	24	5	1,400	19,388
28	13	1,600	10,769	28	11	1,600	12,628	28	8	1,600	16,523	28	7	1,600	19,916	28	6	1,600	22,158
32	15	1,800	12,116	32	12	1,800	14,207	32	10	1,800	18,588	32	8	1,800	22,406	32	7	1,800	24,928
36	17	2,000	13,462	36	14	2,000	15,785	36	11	2,000	20,654	36	9	2,000	24,895	36	8	2,000	27,697
40	18	2,200	14,808	40	16	2,200	17,364	40	12	2,200	22,719	40	10	2,200	27,385	40	9	2,200	30,467
44	20	2,400	16,154	44	17	2,400	18,942	44	13	2,400	24,784	44	11	2,400	29,874	44	10	2,400	33,237
48	22	2,600	17,500	48	19	2,600	20,521	48	14	2,600	26,850	48	12	2,600	32,364	48	11	2,600	36,007
52	24	2,800	18,847	52	20	2,800	22,099	52	16	2,800	28,915	52	13	2,800	34,853	52	11	2,800	38,776
56	26	3,000	20,193	56	22	3,000	23,678	56	17	3,000	30,981	56	14	3,000	37,343	56	12	3,000	41,546
60	28	3,200	21,539	60	23	3,200	25,257	60	18	3,200	33,046	60	15	3,200	39,832	60	13	3,200	44,316
64	29	3,400	22,885	64	25	3,400	26,835	64	19	3,400	35,111	64	16	3,400	42,322	64	14	3,400	47,086
68	31	3,600	24,231	68	27	3,600	28,414	68	20	3,600	37,177	68	17	3,600	44,811	68	15	3,600	49,855
72	33	3,800	25,577	72	28	3,800	29,992	72	22	3,800	39,242	72	18	3,800	47,301	72	16	3,800	52,625
76	35	4,000	26,924	76	30	4,000	31,571	76	23	4,000	41,307	76	19	4,000	49,790	76	17	4,000	55,395
80	37	4,200	28,270	80	31	4,200	33,149	80	24	4,200	43,373	80	20	4,200	52,280	80	18	4,200	58,165
84	39	4,400	29,616	84	33	4,400	34,728	84	25	4,400	45,438	84	21	4,400	54,769	84	18	4,400	60,934
88	40	4,600	30,962	88	34	4,600	36,306	88	26	4,600	47,504	88	22	4,600	57,259	88	19	4,600	63,704
92	42	4,800	32,308	92	36	4,800	37,885	92	28	4,800	49,569	92	23	4,800	59,748	92	20	4,800	66,474
96	44	5,000	33,654	96	37	5,000	39,463	96	29	5,000	51,634	96	24	5,000	62,238	96	21	5,000	69,244
100	46			100	39			100	30			100	25			100	22		

Output speed and torque specifications are THEORETICAL. Speed and torque output are dependent on the overall system efficiencies associated with the prime movers hydraulic system. This document should be used for information and comparative purposes only. When determining criteria, & application specific information is required, please contact DIGGA.

# HIGH POWERED ANCHOR DRIVES SINGLE SPEED - 15-30T

**DIGGA**  
CONSTRUCTION GRADE  
MACHINERY ATTACHMENTS



## INTEGRATED ENERGY CONTROL VALVE INSIDE MANIFOLD



*This revolutionary bypass valve is fitted to the drive to control the rapid decompression of oil caused by pile kick-back during the screw anchoring process.*

### WHY YOU NEED ECV

When the anchor reaches desired torque or depth the operator stops the drive unit, at this stage the anchor has built up a rotational energy (somewhat like a rubber band on a wind-up model plane). This energy that is stored in the anchor needs to be released before the drive unit is disconnected. The ECV bypasses the stored energy allowing the anchor to "unwind" in a controlled manner.

Without this valve, the pressure contained when holding the pile in place would be forced up the pile and into the drive unit resulting in potential damage & costly repairs for the motor and gearbox.

### FEATURES

- Protects motor from rapid oil decompression
- Easily converts your auger drive into a dedicated screw anchor drive

### IDEAL USE

- Screw piling / anchoring

### MACHINE SUITABILITY

- Digga's Energy Control Valve can be fitted to all Digga drilling drive units for screw anchoring applications. ECV comes standard on all Digga anchor drives.

